

Compression Sprayer PCO SERIES 5L / 4L / 2L

Choose Airofog PCO series sprayers, and experience the quality and durability of these beautifully engineered sprayers.

Airofog PCO sprayers are designed for the professional pest control operator to deliver outstanding performance. The sprayers are finished to a very high standard and present a highly professional appearance to clients. All wetted parts are made of chemical resistant materials such as Viton™, Teflon™, high grade stainless steel, brass, and other engineered materials. A cable-operated DRIP-FREE nozzle shut off actuated by the trigger valve provides maximum operator safety and environmental security. The trigger valve can also be simply locked on or off for added safety.



Easy Filling !!!

NEW

wide-mouth opening:
Ø2.3/4 inch (Ø70 mm)
6 inch² (38.5 cm²)

comparing to traditional opening:
Ø1.3/4 inch (Ø45.5 mm)
2.5 inch² (16.3 cm²)



Model example:

| A4DFC9-M / 4DFC9-M | A5HD-A / 5HD-A |
|---|---------------------------------|
| A: for worldwide ; without A: for worldwide except for USA market | |
| 4: 4 litre tank capacity | 5: 5 litre tank capacity |
| DFC: drip-free trigger valve with cable | HD: heavy-duty trigger valve |
| 9: 9" spray lance (18-18") | A: adjustable cone nozzle |
| M: multi-nozzle (F: fan nozzle) | (M: multi-nozzle F: fan nozzle) |

| | 2 Litre | 4 Litre | 5 Litre |
|-----------------------|--|-----------------------|--------------------|
| Working Capacity | 2L, 0.5 US gal. | 4L, 1 US gal. | 5L, 1.3 US gal. |
| Tank Volume | 3L, 0.8 US gal. | 5L, 1.32 US gal. | 6.85L, 1.8 US gal. |
| Tank Material | stainless steel AISI 304 | | |
| Max. Working Pressure | 6 bar, 90 psi | | |
| Pressure Relief Valve | operates at 4 bar, 60 psi | | |
| Pressure Gauge | 0-7 bar, 0-100 psi | | |
| Pump Handle | brass, D-type | | |
| Pump Cylinder | AISI 304 with Viton™ check-valve | | |
| Spray Hose | swivelable, 120 cm | | |
| Trigger Valve | brass; DFC: drip-free type; HD: heavy-duty type | | |
| Spray Lance | AISI 304; DFC: 9" or 18", 23 or 45.8 cm; HD: 50cm | | |
| Nozzle | DFC/HD: 4-way multi-nozzle or even flat fan nozzle 8002E; HD: adjustable cone nozzle | | |
| Carrying Strap | single shoulder strap | double shoulder strap | |
| Service Kit | supplied as standard: pump kit, trigger valve kit, seal/gasket kit | | |
| Tank Dimensions | Ø17 x H18.5 cm | Ø17 x H28.5 cm | Ø17 H36 cm |
| Total Height | 27 cm | 37 cm | 44.5 cm |
| Net Weight | 2.6 kg | 3.2 kg | 3.5 kg |

※ Specifications are subject to change without notice or liability.